

**DIGISTAR PES HD MAGENTA (CC 1000)**

Version 1

Print Date 9/14/2004

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING****Product information**

Product name : DIGISTAR PES HD MAGENTA (CC 1000)

Product code : M408530L001000

Company : Lechler SpA - Luisago  
Via A. De Gasperi 1  
22070 Luisago

Telephone : +39031586111

Telefax : +39031586206

In order to get more information and in case of emergencies please address to Lechler Group Security Office. (Tel. +39-031-586.301).

: Tel. +39-031-586301  
Fax +39-031-586299

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical nature** : Digital screen printing ink

**Hazardous components** :

Components	CAS-No.	EEC-No.	Symbol(s):	R-phrases(s)	Concentration [%]
Octylphenoxyethoxyethanol	9036-19-5		Xn, N	R22, R41, R53	>= 1 - < 3

**3. HAZARDS IDENTIFICATION**

No hazardous preparation according to EC-directive 67/548 and 1999/45/EWG and subsequent amendments.

**4. FIRST AID MEASURES**

General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.

After Inhalation : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious place in recovery position and seek medical advice.

- After Skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- After Eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
Remove contact lenses.  
Seek medical advice.  
Put eye-washer on working place
- After Ingestion : If accidentally swallowed obtain immediate medical attention.  
Keep at rest.  
Do not induce vomiting.

### 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Keep containers and surroundings cool with water spray.
- Extinguishing media which must not be used for safety reasons : Do NOT use water jet.
- Specific hazards during fire fighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Use personal protective equipment.  
Ventilate the area.  
Refer to protective measures listed in sections 7 and 8.  
Material can create slippery conditions.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Additional advice : Refer to section 15 for specific national regulation.

## 7. HANDLING AND STORAGE

### Handling

Safe handling advice : Avoid exceeding of the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

### Storage

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with the particular national regulations.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
No smoking.  
Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Personal protective equipment

Respiratory protection : Provide adequate ventilation.

Hand protection : For prolonged or repeated contact use protective gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Flash point	:	> 63 - 100 °C
Density	:	1,08 g/cm <sup>3</sup>
Viscosity	:	<= 60 s Transversale section: 6 mm Method: 2431 '84 (ISO 6)
Solids by weight	:	40 %

#### 10. STABILITY AND REACTIVITY

Conditions to avoid	:	Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
Hazardous reactions	:	Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity	:	Inhalation of airborne droplets may cause irritation of the respiratory tract.
Skin irritation	:	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.
Note	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

#### 12. ECOLOGICAL INFORMATION

Further information	:	The product contains dangerous substances for the environment (see chapter n° 2), The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.
---------------------	---	---

Octylphenoxyethoxyethanol R53 May cause long-term adverse effects in the aquatic environment.

**13. DISPOSAL CONSIDERATIONS**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

**14. TRANSPORT INFORMATION**

**ADR** : Not classified as dangerous in the meaning of transport regulations.  
**IMDG** : Not classified as dangerous in the meaning of transport regulations.  
**IATA** : Not classified as dangerous in the meaning of transport regulations.

**15. REGULATORY INFORMATION**

Hazardous components which must be listed on the label:

**National legislation**

Germany

Risk classification according to VbF (Germany) : AIII  
Water contaminating class : highly water endangering

No hazardous preparation according to EC-directive 67/548 and 1999/45/EWG and subsequent amendments.

**16. OTHER INFORMATION**

**Further information**

Octylphenoxyethoxyethanol R22 Harmful if swallowed.  
R41 Risk of serious damage to eyes.  
R53 May cause long-term adverse effects in the aquatic environment.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**DIGISTAR PES HD MAGENTA (CC 1000)**

Version 1

Print Date 9/14/2004

Version: 1.3

Revision date 19.02.2003

SDS updated to the 28th adjustment EEC directive 1999/45/CE.